5302 IP Phone

Slim, dual-port, two-line, entry-level IP phone.

The Mitel[®] 5302 IP Phone is an economical, entry-level IP desktop device that takes advantage of the cost savings of a converged network infrastructure. It provides basic telephony features and PC connectivity in a two-line phone.

It is ideal for locations that only need basic call handling features, e.g., as a point of sale phone for the retail market, as a second guestroom phone for the hospitality market, a classroom phone, a patient room phone. The phone's footprint is smaller than other IP phones, and it can be desktop or wall mounted.

Two Line, Two Ports

Handle more than one incoming call with the 5302 IP Phone's two lines, and still use voice mail as a backup option. Dual-port capability means only a single LAN drop is required for both voice and data – no need for additional wiring to add a PC.

IP Paging

Though it is an entry-level phone, the 5302 IP Phone provides important user-friendly paging features that are applicable in multiple environments (e.g., healthcare, schools).

Additional Features

- 2 lines with LED indication
- 3 fixed feature keys: hold, redial, transfer
- 4 programmable keys: e.g., speed dials, feature access codes, paging, conferencing, voice mail access
- Paging and page receive capability
- Set to set paging
- V4 handset (3.4 KHz)
- Incoming call visual indication
- Message waiting indication
- Adjustable volume up / down
- Adjustable ringing up / down
- Adjustable speaker (paging) volume
- 12-button numeric keypad
- Speaker for receiving pages
- SIP protocol
- Security: SIP authentication
- Support for DHCP addressing
- Wall mountable (optional)
- Multiple powering options (802.3af compliant)
- ADA compliant (hearing aid compatible (HAC) handset)
- Small footprint (19cm x 10cm or 7.5" x 4")



3300 ICP System Requirements

- Mitel 3300 IP Communications Platform (ICP), Release 8.0 (UR2)
- The maximum number of 5302 IP Phones supported on the various 3300 Controllers is as follows:

| Controller | Maximum Number of IP Devices | Maximum Number of 5302 IP Phone Devices |
|---|---------------------------------|---|
| 3300 CX Controller / 3300 CXi Controller | 100 | 100 |
| 3300 AX Controller | 100 | 100 |
| 3300 MXe Controller Standard | 300 | 300 |
| 3300 MXe Controller Expanded | 1,400 | 1,000* |
| 3300 MXe Server | 5,000 | 1,000* |

* This is a SIP license limitation.

Regulatory Standards

EMC: CANADA: ICES-003 Issue 3

> USA: CFR Title 47, Part 15 (CLASS B)

EU: R&TTE directive (1999/5/EC) EN55024: 1998 + A1 + A2 Class B EN55022: 1998 + A1 + A2

Safety: CANADA: CAN/CSA-C22.2 No. 60950-00

> USA: UL60950 ANSI/NFPA 70

EU: R&TTE directive (1999/5/EC) EN60950: 2000

EN61000 - 3 - 2 : 2000 EN61000 - 3 - 3 : 1995 + A1 : 2001 EN61000 - 4 - 2 : Level 4

5302 IP Phone Specifications

| Ports | Power | Power Consumption | Processor Type | Processor Speed | DSPs | DSP Speed |
|---|---|-------------------|---|--------------------------------------|--|-----------------------------|
| 2 10/100 Mb switched ethernet | 802.3 af Power over Ethernet (PoE) compliant | 3.84W | MIPS32 4Kc RISC CPU | 150 MHz | 16-bit fixed point OAK [®] DSP | 100 MHz |
| Silicon | RAM | ROM | Voice Traffic | Signaling | Voice QoS | Size (LxWxH) |
| Infineon INCA IPs Processor (PSB 21553 | 16 MB 3 V1.4) | 8 MB | RTP over UDP | Session Initiation Protocol (SIP) | IEEE 802.1p/q | 7.5"x4"x3" 19cmx10cmx8cm |
| Weight | MTBF Rate | Compression | Storage | | General Worki | ng |
| 1.1 lbs. (550g) | 25 Years | G.711, G.729 | Temp: -40°C to +66°C Humidity: 15% at +66°C, 95% at 29°C | | Temp: +4°C to +49°C Humidity: 34% at +49°C, 95% at 29°C | |

| | ricas Headquai orate Headqua | |
|--------|---------------------------------|--|
| Tel: + | 1 613-592-2122 | |
| Fax: + | 1 613-592-4784 | |

Europe, Middle East and Africa Headquarters Tel: +44 (0) 1291 430000 Fax: +44 (0) 1291 430400

For more information on our worldwide office locations, visit our website at www.mitel.com/offices

Asia Pacific Headquarters Tel: +852 2508 9780 Fax: +852 2508 9232

www.mitel.com

VTHIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.



M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2007, Mitel Networks Corporation. All Rights Reserved.