

MITEL

IP Programmable Key Modules

Improve call handling with Programmable Key Modules for the Mitel 5224 and 5235 IP Phones



The Mitel® IP Programmable Key Modules (PKM) extend the capability of the Mitel 5224 and 5235 IP Phones with additional buttons. Ideal for receptionists, departmental administrative assistants, and people who require additional personal keys, PKMs can be easily programmed through the phone and can be used to monitor and manage multiple lines beyond the capacity of the 5224 and 5235 IP Phones.

Improve Call Handling

Administrative assistants can use the 12- and 48-button IP PKMs to monitor and manage multiple lines beyond the 24-line capacity of the 5224 and 5235 IP Phones. The 12-button IP PKM adds 12 keys while the 48-button IP PKM adds 48 additional keys with one module, and 96 keys with two modules connected to a 5224 or 5235 IP Phone.

A IP PKM Interface Module added to the back of a 5224 or 5235 IP Phone allows the 12- and 48-button IP PKMs to easily connect to an IP phone, without the need for an additional LAN port.

When used in either an enterprise or small business environment, the IP PKMs improve call handling for both employees and customers.

Easily Programmed

With the PKMs, 12, 48 or 96 additional keys can be easily programmed as feature keys, speed call keys, extension keys, Direct Station Select (DSS) keys, or line appearance keys. Each key has an associated indicator light, which gives the status of that extension or programmed feature. Personal keys can be easily programmed through the IP phones themselves or the web browser-based configuration tool of the 5224 IP Phone.



it's about **YOU**

Physical Characteristics

IP PKM (12 Button):

Dimensions: 6.75 in. x 2.25 in (17 cm x 5.7 cm)

Weight: 0.6 lbs. (0.3 kg)

IP PKM (48 Button)

Dimensions: 7.25 in x 9.25 in (18.4 cm x 23.5 cm)

Weight: 2.1 lbs (0.9 kg)

Voice QoS

IEEE 802.1 p/q

Powering Options

5224 IP Phone:

- Powered via the adapter power port or Powered over Ethernet with a power source compliant to IEEE 802.3af
- 24VDC power adapter or 48VDC Ethernet Power Adapter available, purchased separately (if required)

5235 IP Phone:

- Powered over Ethernet with a power source compliant to IEEE 802.3af
- 48VDC Ethernet Power Adapter available, purchased separately (if required)

System Requirements:

- Mitel 3300 IP Communications Platform (ICP), Release 6.1 or later
- Mitel SX-200 IP Communications Platform (ICP), Release 3.0 or later

North America

Tel: (613) 592 2122
Fax: 1 800 648 3579

Benelux

Tel: +31 (0)30 85 00 030
Fax: +31 (0)30 85 00 031

Middle East

Tel: +971 4 3916721
Fax: +971 4 3915288

Latin America

Tel: (613) 592 2122
Fax: 1 800 648 3579

Italy

Tel: +39 02 2130231
Fax: +39 02 21302333

South Africa

Tel: +27 82 559 8688
Fax: +27 11 784 6916

UK

Tel: +44 (0)1291 430000
Fax: +44 (0)1291 430400

Germany, Switzerland, Austria

Tel: +49 (0)211 5206480
Fax: +49 (0)211 52064899

Asia-Pacific

Tel: +852 2508 9780
Fax: +852 2508 9232

France

Tel: +33 (0)1 61 37 00 90
Fax: +33 (0)1 61 37 00 99

Portugal and Spain

Tel: +34 91 490 5300
Fax: +34 91 490 5301

South Pacific

Tel: +61 2 9023 9500
Fax: +61 2 9023 9501

www.mitel.com



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. The information furnished in this document, believed by Mitel to be accurate as of the date of its publication, is subject to change without notice. Mitel assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

M MITEL (design) is a registered trademark of Mitel Networks Corporation. All other products and services are the registered trademarks of their respective holders.

© Copyright 2006, Mitel Networks Corporation. All Rights Reserved.

GD 10975 PN 51006101RC-EN